



KONICA MINOLTA

# bizhub C35

✍ A4 colour multifunctional

✍ 30 pages per minute in colour and black & white

## ✍ Functionality



- Colour
- Black & white

Copying



- Colour
- Black & white
- PCL/PS
- Local/network
- USB

Printing



- TWAIN Network
- Scan-to-SMB
- Scan-to-eMail
- Scan-to-FTP
- Scan-to-WebDAV
- Scan-to-USB
- Scan-to-HDD

Scanning



- i-Fax
- PC-Fax
- Super G3 Fax


Faxing



**Technology**

EMPERON™ ✓	SIMITRI® HD TONER ✓	IWS ✗	OPEN API ✓	i-OPTION ✗	CSRC ✓
---------------	------------------------	----------	---------------	---------------	-----------

**Option diagram**



**Finishing options**



Duplex

## Descriptions

<b>bizhub C35</b>	A4 communicator with 30 ppm in b/w and colour. Standard Emperon controller with PCL, PostScript and XPS support. Paper capacity of 250 + 100 sheets. Automatic duplex unit and automatic duplex feeder standard. 1.5 GB memory and 250 GB hard disc and Gigabit Ethernet standard.
-------------------	--

<b>PF-P08 Lower paper feeder</b>	A4, 500 sheets, up to 90 gsm
<b>DK-P01 Simple cabinet</b>	Ensures ergonomic height and provides paper storage capacity
<b>WT-P01 Working table</b>	For authentication device placement
<b>IC-Card reader</b>	Various card technologies
<b>EH-C591 Convenience stapler</b>	Convenient stapling of up to 50 prints per set
<b>SX-600 Wireless LAN</b>	Wireless LAN to network connector

## Technical specifications

### COPIER SPECIFICATIONS

<b>Copying process</b>	Electrostatic laser copy; Tandem, indirect
<b>Toner system</b>	Simitri® HD polymerised toner
<b>Copy/print speed A4 (mono/colour)</b>	Up to 30/30 ppm
<b>Auto duplex speed A4 (mono/colour)</b>	Up to 30/30 ppm
<b>1st copy time (mono/colour)</b>	10.1/12.0 sec.
<b>Warm-up time</b>	Approx. 45 sec.*
<b>Copy resolution</b>	600 x 600 dpi
<b>Gradation</b>	256 gradations
<b>Multi-copy</b>	1 – 999
<b>Original format</b>	Max. A4
<b>Magnification</b>	25 – 400% in 0.1% steps
<b>Copy functions</b>	Duplex copy; 2in1; 4in1; proof copy; program/recall jobs; density adjustment; electronic collation; ID Copy

### PRINTER SPECIFICATIONS

<b>Print resolution</b>	600 x 600 dpi x 3 bit
<b>1st print time (mono/colour)</b>	12.9/12.9 sec.
<b>Controller CPU</b>	800 MHz
<b>Page description languages</b>	PostScript 3 (CPSI 3016) PCL6 (XL 3.0); PCL5e/c XPS PDF Direct Printing (Version 1.7) JPEG/TIFF Direct Print
<b>Operating systems</b>	Windows 2000 Windows XP (32/64) Windows Vista (32/64) Windows 7 (32/64) Windows Server 2003 (32/64) Windows Server 2008 (32/64) Windows DPWS Support Macintosh OSX 10.x Linux: Redhat, SUSE Citrix Netware 4, 5, 6
<b>Printer fonts</b>	80 PCL Latin; 137 PostScript 3 Emulation Latin
<b>Print functions</b>	Direct print of PDF (version 1.7); JPEG; TIFF; XPS; overlay; watermark; n-up; poster; booklet page order; collating

### SCANNER SPECIFICATIONS

<b>Scan speed</b>	Up to 30 opm (300 dpi via DF)
<b>Scan resolution</b>	Max.: 600 x 600 dpi
<b>Scan modes</b>	Network TWAIN scan WIA scan Scan-to-eMail Scan-to-FTP Scan-to-SMB Scan-to-HDD Scan-to-WebDAV Scan-to-DPWS Scan-to-USB
<b>File formats</b>	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS
<b>Scan destinations</b>	Up to 2,000 (single); up to 100 (group); LDAP support
<b>Scan functions</b>	Up to 400 job programs



**FAX SPECIFICATIONS**

<b>Fax standard</b>	Super G3
<b>Fax transmission</b>	Analogue; PC-Fax; i-Fax
<b>Fax resolution</b>	Max.: 400 x 400 dpi (super-fine)
<b>Fax compression</b>	MH; MR; MMR; JBIG
<b>Fax modem</b>	Up to 33.6 Kbps
<b>Fax destinations</b>	Up to 2,000 (single); up to 100 (group)
<b>Fax functions</b>	Time shift; fax forwarding; up to 400 job programs

**SYSTEM SPECIFICATIONS**

<b>System memory</b>	1.5 GB
<b>System hard disc</b>	250 GB
<b>Interface</b>	10-Base-T/100-Base-TX/1000-Base-T Ethernet; USB 2.0
<b>Network protocols</b>	TCP/IP (IPv4 / IPv6); IPX/SPX; AppleTalk (EtherTalk); SMB; LPD; IPP; SNMP; HTTP; HTTPS
<b>Frame types</b>	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP
<b>Automatic document feeder</b>	Up to 50 originals A5 – A4 (140 – 216 x 148 – 355.6 mm); 50 – 128 gsm
<b>Printable paper size</b>	A6 – A4; customised paper sizes
<b>Printable paper weight</b>	60 – 210 gsm
<b>Paper input capacity</b>	Standard: 350 sheets Max.: 1,350 sheets
<b>Tray 1</b>	250 sheets; A6 – A4; 60 – 210 gsm; Custom sizes (92 – 216 x 148 – 297 mm)
<b>Tray 2 (optional)</b>	500 sheets; 60 – 90 gsm; A4
<b>Tray 3 (optional)</b>	500 sheets; 60 – 90 gsm; A4
<b>Manual bypass</b>	100 sheets; A6 – A4; 60 – 210 gsm; Custom sizes (92 – 216 x 148 – 356 mm)
<b>Automatic duplexing</b>	A4; 60 – 210 gsm
<b>Output capacity</b>	Max. 250 sheets face-down
<b>Copy/print volume (monthly)</b>	Recommended: 1,920 pages Max.: 120,000 pages
<b>Toner lifetime**</b>	Black/CMY yield up to 6,000 pages
<b>Imaging unit lifetime</b>	Black/CMY yield up to 30,000 pages
<b>Power consumption</b>	220-240 V / 50/60 Hz; less than 1.3 KW
<b>System dimensions (W x D x H, mm)</b>	530 x 508 x 550
<b>System weight</b>	Approx. 39 kg

**SYSTEM FEATURES**

<b>Security</b>	ISO15408 EAL3 IP filtering and port blocking SSL2, SSL3 and TLS 1.0 network communication IPsec support IEEE 802.1x support User authentication Secure print Hard disc overwrite (8 standard types) Hard disc data encryption (AES 128) Copy protection (print only)
<b>Accounting</b>	Up to 1,000 (users + accounts) Active Directory; NTLM V.1; NTLM V.2; NDS; LDAP support User function access definition IC-Card authentication
<b>Software</b>	PageScope Net Care Device Manager PageScope Data Administrator PageScope Direct Print Print Status Notifier

\*Warm up time may vary depending on the operating environment and usage  
\*\*Declared yield in accordance with ISO/IEC 19798

- All specifications refer to A4-size paper of 80 gsm quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any prices or specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

